



445/95 R 25 174 F CR-01 TL

- Open tread block design for excellent traction
- Mitas-Link, unique connection between tread blocks ensuring extended tire life
- Deepest tread pattern in category
- Reduced fuel consumption thanks to all-steel construction improving rolling resistance
- Improved operator comfort and low noise emissions in road high speed service
- Easy self-cleaning in off-road application
- Regroovable and suitable for retreading thanks to high durability of carcass
- Homologated as M + S and meets requirements for winter conditions
- Fully homologated according to EU Directives 92/93, 2001/43 and 2005/11 (noise homologation)

TECHNICAL DATA

EAN code	8590341044815	Tire size	445/95 R 25
Tread pattern	CR-01	Alternative tire size	
Service description	174 F	Permitted rims	11.00/1.7CR-25 11.25/2.0-25 11.00/1.7CRx25
Type	TL	Overall diameter - new tire (mm)	1480
Overall diameter - max in service (mm)	1570	Section width - new tire (mm)	440
Section width - max in service (mm)	483	Rolling circumference (mm)	4504
Static radius (mm)	688	Tread depth (mm)	26

LOAD CAPACITY PER TYRE

Tire load (kg) at pressure (bar)					Speed (km/h)
5.00	6.00	7.00	8.00	9.00	
4135	4820	5360	6010	6500	85
10395	12125	13590	15160	16750	0 Static
8780	10255	11465	12795	14070	5
7575	8855	9885	11035	12060	10
6360	7430	8280	9255	10050	20
5320	6215	6915	7740	8375	30
4900	5720	6365	7125	7705	40
4775	5570	6195	6940	7505	50
4685	5470	6075	6815	7370	60
4475	5220	5805	6510	7035	70
4260	4970	5525	6195	6700	80